

Multiple heads Mehrspindelköpfe

V.FP - FIXED CENTRES HEADS V.FP - FESTE BOHRKÖPFE

Type Typ	Steel 500 N/mm ² Steel 500 N/mm ²		Min. centres distance Min. Achsabstand	Ø A	Ø B	Ø C	L1	L2	L3	Type Typ	Capacity Spannbereich
	Ø	M									
V.FP1.*.11.P	5	5	16	16	16	22	156	42	10	ER 11	0,5 ÷ 7
V.FP2.*.11.P	7	7	20	18	20	26	153	39	9	ER 11	0,5 ÷ 7
V.FP1.*.16.P	9	8	24	22	24	30	163	49	9	ER 16	0,5 ÷ 10
V.FP2.*.16.P	10	8	27	24	27	33	167	48	8	ER 16	0,5 ÷ 10
V.FP1.*.20.P	12	10	31	28	31	37	183	64	19	ER 20	1 ÷ 13
V.FP2.*.20.P	12	10	34	28	34	40	183	64	19	ER 20	1 ÷ 13
V.FP1.*.25.P	14	12	38	34	38	44	190	71	22	ER 25	1 ÷ 16
V.FP2.*.25.P	18	14	46	42	46	53	186,5	62,5	22	ER 25	1 ÷ 16
V.FP1.*.32.P	20	16	50	50	50	56	196,5	72,5	26	ER 32	1 ÷ 20
V.FP2.*.32.P	20	16	52	47	52	69,5	182	58	23	ER 25	1 ÷ 16

